

**Amendments to the Claims:**

The listing of claims replaces all prior versions, and listings, of claims in the application:

**Listing of Claims:**

- 1 1. (Currently Amended) A method for correlating services within a computer network, the  
2 method comprising:  
3 providing a message interchange network for exchanging application-level messages  
4 between services, the message interchange network which manages managing a plurality of  
5 services which are each accessible by a plurality of services; and  
6 tracking correlation information regarding each application-level message received into  
7 message interchange network, wherein the application-level messages are being sent between  
8 pairs of the services, wherein the correlation information for each application-level message  
9 pertains to each application-level message and any other application-level messages related to  
10 the each application-level message.
- 1 2. (Currently Amended) A method as recited in claim 1, wherein the correlation  
2 information for each application-level message includes message information regarding the each  
3 application-level message and/or call information regarding a call to which the each application-  
4 level message and any other related application-level message belongs, and/or session  
5 information regarding a session to which the each application-level message and any other  
6 related application-level message belongs.
- 1 3 (Currently Amended) A method as recited in claim 2, wherein the message information  
2 for each application-level message includes a Hop Identifier (ID) uniquely identifying a hop  
3 between a sender and receiver of the each application-level message.
- 1 4. (Currently Amended) A method as recited in claim 3, wherein the message information  
2 for each application-level message further includes an identification of the each application-level  
3 message's sending service and receiving service.

1 5. (Currently Amended) A method as recited in claim 3, wherein the message information  
2 for each application-level message further includes an indication as to whether the each  
3 application-level message has completed transmission.

1 6. (Currently Amended) A method as recited in claim 5, wherein the message information  
2 for each application-level message further includes a reason or error log regarding why the each  
3 application-level message has failed to complete its transmission if the each application-level  
4 message has failed.

1 7. (Currently Amended) A method as recited in claim 3, wherein the message information  
2 for each application-level message further includes a portion of the each message content.

1 8. (Currently Amended) A method as recited in claim 3, wherein the message information  
2 for each application-level message further includes two or more of the following: an  
3 identification of the each application-level message's sending and receiving service, an  
4 indication as to whether the each application-level message has completed transmission, a reason  
5 or error log regarding why the each application-level message has failed to complete its  
6 transmission if the each application-level message has failed, and a portion of the each  
7 application-level message content, a size of the each application-level message, a topic of the  
8 each application-level message, a status on processing steps taken on the each application-level  
9 message, and specification of any protocols used in receiving and sending the each application-  
10 level message.

1 9. (Original) A method as recited in claim 2, wherein the call information for each call  
2 includes a Call Identifier (ID) uniquely identifying the each call.

1 10. (Original) A method as recited in claim 9, wherein the call information for each call  
2 further includes two or more of the following: an indication as to whether the each call is  
3 complete and a reason for the call not being complete if the each call fails to complete, a type of  
4 each call, a receiving and sending time for the each call, a sender and recipient service of each  
5 call, a status of policy evaluation for each call, and a set of hops in each call.

1 11. (Original) A method as recited in claim 2, wherein the session information for each  
2 session includes a Session Identifier (ID) uniquely identifying the each session.

1 12. (Original) A method as recited in claim 11, wherein the session information for each  
2 session further includes an indication as to whether the each session is complete and a reason for  
3 the session not being complete if the each session fails to complete.

1 13. (Currently Amended) A method as recited in claim 11, wherein the session information  
2 for each session further includes a calculated or executed route for application-level messages  
3 sent within the each session.

1 14. (Original) A method as recited in claim 11, wherein the session information for each  
2 session further includes an identity and status of each service of the each session.

1 15. (Original) A method as recited in claim 11, wherein the session information for each  
2 session further includes two or more of the following: an indication as to whether the each  
3 session is complete and a reason for the session not being complete if the each session fails to  
4 complete, a calculated or executed route for messages sent within the each session, and an  
5 identity and status of each service of the each session, an initiating time and completion time for  
6 each session, and an indication of a set of calls in each session.

1 16. (Original) A method as recited in claim 2, wherein each message belongs to a particular  
2 call between two of the services.

1 17. (Currently Amended) A method as recited in claim 2, wherein each call ~~may~~ includes a  
2 request message and a response message or a notification message.

1 18. (Currently Amended) A method as recited in claim 2, wherein a call is defined as a set of  
2 predefined application-level message types.

1 19. (Currently Amended) A method as recited in claim 2, wherein a session is determined by  
2 the services which send application-level messages for the set of calls as a set of calls.

1 20. (Original) A method as recited in claim 1, wherein at least some of services are  
2 implemented on different computer systems and at least some of these computer systems differ  
3 from a computer system which implements the message interchange network.

1 21. (Currently Amended) A method as recited in claim 2, wherein the tracking of correlating  
2 information comprises:

3 receiving a current application-level message at the message interchange network,  
4 wherein the current application-level message belongs to a current session and a current call;  
5 when ~~this~~ the received current application-level message is a first message received for  
6 the current session, assigning a session identifier for the current message and embedding the  
7 session identifier in the current application-level message prior to forwarding it the application-  
8 level message to its destination service;

9 when ~~this~~ the received current application-level message is a first message received for  
10 the current call, assigning a call identifier for the current application-level message and  
11 embedding the call identifier in the current application-level message prior to forwarding it the  
12 application-level message to its destination service;

13 assigning a hop identifier for the current application-level message which uniquely  
14 identifies the current application-level message; and

15 associating and storing the session identifier, the call identifier, and the hop identifier,  
16 along with message information, call information, and session information for the received  
17 application-level message.

1 22. (Original) A method as recited in claim 2, further comprising:

2 receiving a query for correlation information regarding a particular session or call,  
3 wherein the query is sent by a first one of the services; and

4 sending correlation information to the first service related to the particular session or call  
5 of the query.

1 23. (Currently Amended) A method as recited in claim 22, wherein the correlation  
2 information includes information regarding application-level messages sent between more than  
3 two services.

1 24. (Original) A method as recited in claim 22, further comprising determining whether the  
2 first service is authorized to make the query and only sending correlation information to the first  
3 service when it is determined that the first service is authorized.

1 25. (Original) A method as recited in claim 1, wherein at least one of the services is a  
2 routing script.

1 26. (Currently Amended) A method as recited in claim 1, wherein the correlation  
2 information includes at least one message identifier specified in at least one of the application-  
3 level messages which is sent by a sending service, the method further comprising:  
4 receiving a query for correlation information regarding a particular message identifier,  
5 wherein the query is sent by a first one of the services; and  
6 sending correlation information to the first service related to the particular message  
7 identifier of the query.

1 27. (Currently Amended) A computer system operable to correlate services within a  
2 computer network the computer system comprising:  
3 one or more processors;  
4 one or more memory, wherein at least one of the processors and memory are adapted for:  
5 providing a message interchange network for exchanging application-level  
6 messages between services, the message interchange network which manages managing a  
7 plurality of services which are each accessible by a plurality of services; and  
8 tracking correlation information regarding each application-level message  
9 received into message interchange network, wherein the application-level messages are  
10 being sent between pairs of the services, wherein the correlation information for each  
11 application-level message pertains to each application-level message and any other  
12 application-level messages related to the each application-level message.

1 28. (Currently Amended) A computer system as recited in claim 27, wherein the correlation  
2 information for each application-level message includes message information regarding the each  
3 application-level message and/or call information regarding a call to which the each application-  
4 level message and any other related application-level message belongs, and/or session  
5 information regarding a session to which the each application-level message and any other  
6 related application-level message belongs.

1 29 (Currently Amended) A computer system as recited in claim 28, wherein the message  
2 information for each application-level message includes a Hop Identifier (ID) uniquely  
3 identifying a hop between a sender and receiver of the each application-level message.

1 30. (Currently Amended) A computer system as recited in claim 29, wherein the message  
2 information for each application-level message further includes two or more of the following: an  
3 identification of the each application-level message's sending and receiving service, an  
4 indication as to whether the each application-level message has completed transmission, a reason  
5 or error log regarding why the each application-level message has failed to complete its  
6 transmission if the each application-level message has failed, and a portion of the each  
7 application-level message content, a size of the each application-level message, a topic of the  
8 each application-level message, a status on processing steps taken on the each application-level  
9 message, and specification of any protocols used in receiving and sending the each application-  
10 level message.

1 31. (Original) A computer system as recited in claim 28, wherein the call information for  
2 each call includes a Call Identifier (ID) uniquely identifying the each call.

1 32. (Original) A computer system as recited in claim 31, wherein the call information for  
2 each call further includes two or more of the following: an indication as to whether the each call  
3 is complete and a reason for the call not being complete if the each call fails to complete, a type  
4 of each call, a receiving and sending time for the each call, a sender and recipient service of each  
5 call, a status of policy evaluation for each call, and a set of hops in each call.

1 33. (Original) A computer system as recited in claim 28, wherein the session information for  
2 each session includes a Session Identifier (ID) uniquely identifying the each session.

1 34. (Original) A computer system as recited in claim 33, wherein the session information for  
2 each session further includes two or more of the following: an indication as to whether the each  
3 session is complete and a reason for the session not being complete if the each session fails to  
4 complete, a calculated or executed route for messages sent within the each session, and an  
5 identity and status of each service of the each session, an initiating time and completion time for  
6 each session, and an indication of a set of calls in each session.

1 35. (Currently Amended) A computer system as recited in claim 31, wherein each call ~~may~~  
2 includes a request message and a response message or a notification message.

1 36. (Original) A computer system as recited in claim 28, wherein a call is defined as a set of  
2 predefined application-level message types.

1 37. (Original) A computer system as recited in claim 36, wherein a session is determined by  
2 the services which send application-level messages for the set of calls as a set of calls.

1 38. (Original) A computer system as recited in claim 27, wherein at least some of services  
2 are implemented on difference computer systems and at least some of these computer systems  
3 differ from a computer system which implements the message interchange network.

1 39. (Currently Amended) A computer system as recited in claim 28, wherein the tracking of  
2 correlating information comprises:

3 receiving a current application-level message at the message interchange network,  
4 wherein the current application-level message belongs to a current session and a current call;  
5 when ~~this~~ the received current application-level message is a first message received for  
6 the current session, assigning a session identifier for the current message and embedding the  
7 session identifier in the current application-level message prior to forwarding ~~#~~ the application-  
8 level message to its destination service;

9 when ~~this~~ the received current application-level message is a first message received for  
10 the current call, assigning a call identifier for the current application-level message and  
11 embedding the call identifier in the current application-level message prior to forwarding ~~#~~ the  
12 application-level message to its destination service;

13 assigning a hop identifier for the current application-level message which uniquely  
14 identifies the current application-level message; and

15 associating and storing the session identifier, the call identifier, and the hop identifier,  
16 along with message information, call information, and session information for the received  
17 application-level message.

1 40. (Original) A computer system as recited in claim 28, wherein the at least one of the  
2 processors and memory are further adapted for:

3 receiving a query for correlation information regarding a particular session or call,  
4 wherein the query is sent by a first one of the services; and

5 sending correlation information to the first service related to the particular session or call  
6 of the query.

1 41. (Original) A computer system as recited in claim 26, wherein at least one of the services  
2 is a routing script.

1 42. (Currently Amended) A computer program product for correlating services within a  
2 computer network, the computer program product comprising:  
3 at least one computer readable medium;  
4 computer program instructions stored within the at least one computer readable product  
5 medium configured for:  
6 providing a message interchange network for exchanging application-level  
7 messages between services, the message interchange network which manages managing a  
8 plurality of services which are each accessible by a plurality of services; and  
9 tracking correlation information regarding each application-level message  
10 received into message interchange network, wherein the application-level messages are  
11 being sent between pairs of the services, wherein the correlation information for each  
12 application-level message pertains to each application-level message and any other  
13 application-level messages related to the each application-level message.

1 43. (Currently Amended) A computer program product as recited in claim 42, wherein the  
2 correlation information for each application-level message includes message information  
3 regarding the each application-level message and/or call information regarding a call to which  
4 the each application-level message and any other related application-level message belongs,  
5 and/or session information regarding a session to which the each application-level message and  
6 any other related application-level message belongs.

1 44 (Currently Amended) A computer program product as recited in claim 43, wherein the  
2 message information for each application-level message includes a Hop Identifier (ID) uniquely  
3 identifying a hop between a sender and receiver of the each application-level message.

1 45. (Currently Amended) A computer program product as recited in claim 44, wherein the  
2 message information for each application-level message further includes an identification of the  
3 each application-level message's sending service and receiving service.



1 46. (Currently Amended) A computer program product as recited in claim 44, wherein the  
2 message information for each application-level message further includes an indication as to  
3 whether the each application-level message has completed transmission.

1 47. (Currently Amended) A computer program product as recited in claim 46, wherein the  
2 message information for each application-level message further includes a reason or error log  
3 regarding why the each application-level message has failed to complete its transmission if the  
4 each application-level message has failed.

1 48. (Currently Amended) A computer program product as recited in claim 44, wherein the  
2 message information for each application-level message further includes a portion of the each  
3 message content.

1 49. (Currently Amended) A computer program product as recited in claim 44, wherein the  
2 message information for each application-level message further includes two or more of the  
3 following: an identification of the each application-level message's sending and receiving  
4 service, an indication as to whether the each application-level message has completed  
5 transmission, a reason or error log regarding why the each application-level message has failed  
6 to complete its transmission if the each application-level message has failed, and a portion of the  
7 each application-level message content, a size of the each application-level message, a topic of  
8 the each application-level message, a status on processing steps taken on the each application-  
9 level message, and specification of any protocols used in receiving and sending the each  
10 application-level message.

1 50. (Original) A computer program product as recited in claim 43; wherein the call  
2 information for each call includes a Call Identifier (ID) uniquely identifying the each call.

1 51. (Original) A computer program product as recited in claim 50, wherein the call  
2 information for each call further includes two or more of the following: an indication as to  
3 whether the each call is complete and a reason for the call not being complete if the each call  
4 fails to complete, a type of each call, a receiving and sending time for the each call, a sender and  
5 recipient service of each call, a status of policy evaluation for each call, and a set of hops in each  
6 call.

1 52. (Original) A computer program product as recited in claim 43, wherein the session  
2 information for each session includes a Session Identifier (ID) uniquely identifying the each  
3 session.

1 53. (Original) A computer program product as recited in claim 52, wherein the session  
2 information for each session further includes an indication as to whether the each session is  
3 complete and a reason for the session not being complete if the each session fails to complete.

1 54. (Currently Amended) A computer program product as recited in claim 52, wherein the  
2 session information for each session further includes a calculated or executed route for  
3 application-level messages sent within the each session.

1 55. (Original) A computer program product as recited in claim 52, wherein the session  
2 information for each session further includes an identity and status of each service of the each  
3 session.

1 56. (Original) A computer program product as recited in claim 52, wherein the session  
2 information for each session further includes two or more of the following: an indication as to  
3 whether the each session is complete and a reason for the session not being complete if the each  
4 session fails to complete, a calculated or executed route for messages sent within the each  
5 session, and an identity and status of each service of the each session, a initiating time and  
6 completion time for each session, an indication of a set of calls in each session.

1 57. (Original) A computer program product as recited in claim 43, wherein each message  
2 belongs to a particular call between two of the services.

1 58. (Currently Amended) A computer program product as recited in claim 43, wherein each  
2 call ~~may~~ includes a request message and a response message or a notification message.

1 59. (Currently Amended) A computer program product as recited in claim 43, wherein a call  
2 is defined as a set of predefined application-level message types.

1 60. (Currently Amended) A computer program product as recited in claim 43, wherein a  
2 session is determined by the services which send application-level messages for the set of calls  
3 as a set of calls.

1 61. (Original) A computer program product as recited in claim 42, wherein at least some of  
2 services are implemented on difference computer systems and at least some of these computer  
3 systems differ from a computer system which implements the message interchange network.

1 62. (Currently Amended) A computer program product as recited in claim 43, wherein the  
2 tracking of correlating information comprises:

3 receiving a current application-level message at the message interchange network,  
4 wherein the current application-level message belongs to a current session and a current call;  
5 when this the received current application-level message is a first message received for  
6 the current session, assigning a session identifier for the current message and embedding the  
7 session identifier in the current application-level message prior to forwarding ~~it~~ the application-  
8 level message to its destination service;

9 when this the received current application-level message is a first message received for  
10 the current call, assigning a call identifier for the current application-level message and  
11 embedding the call identifier in the current application-level message prior to forwarding ~~it~~ the  
12 application-level message to its destination service;

13 assigning a hop identifier for the current application-level message which uniquely  
14 identifies the current application-level message; and

15 associating and storing the session identifier, the call identifier, and the hop identifier,  
16 along with message information, call information, and session information for the received  
17 application-level message.

1 63. (Currently Amended) A computer program product as recited in claim 43, wherein the ~~at~~  
2 ~~least one~~ computer readable product ~~are~~ is further configured for:

3 receiving a query for correlation information regarding a particular session or call,  
4 wherein the query is sent by a first one of the services; and

5 sending correlation information to the first service related to the particular session or call  
6 of the query.

1 64. (Currently Amended) A computer program product as recited in claim 63, wherein the  
2 correlation information includes information regarding application-level messages sent between  
3 more than two services.

1 65. (Currently Amended) A computer program product as recited in claim 63, wherein the at  
2 least ~~one~~ computer readable product ~~are~~ is further configured for determining whether the first  
3 service is authorized to make the query and only sending correlation information to the first  
4 service when it is determined that the first service is authorized.

1 66. (Original) A computer program product as recited in claim 42, wherein at least one of  
2 the services is a routing script.

1 67. (Currently Amended) A computer program product as recited in claim 42, wherein the  
2 correlation information includes at least one message identifier specified in at least one of the  
3 application-level messages which is sent by a sending service, the method further comprising:  
4 receiving a query for correlation information regarding a particular message identifier,  
5 wherein the query is sent by a first one of the services; and  
6 sending correlation information to the first service related to the particular message  
7 identifier of the query.